

ROCK-SOLID RELIABILITY

BigTow[®] TRAILERS



Description:

The Big Tow[®] deck-over tilt trailers offer convenience and durability. There are no ramps to hassle with, simply tilt the deck, drive on or off and level the deck back down. It features our patented automatic kick-out ramp that doubles as an under-ride protection bumper. The tilt deck trailer features a single-lever twin-latch system, stationary forward deck, Hutchens[®] suspension and adjustable hitch. A deck cushion cylinder eases the deck back into transport position and prevents equipment from slamming the deck down.

Quick Specs:

- 36" deck height (empty)
- 8'-6" deck width
- Tilt deck cushion cylinder
- Air brakes
- Hutchens[®] suspension
- Auto kick-out ramp/under-ride protection
- Single-lever twin-latch locking system
- LED lights and sealed wiring



Patented automatic kick-out ramp doubles as under-ride protection.




Cushion cylinder controls the deck from slamming when loading or unloading equipment.



Standard 4-foot stationary deck gives room for longer equipment and makes towing easier.

Go directly to our web site with your Smart Phone. Scan this tag with your phone's camera using the app at <http://gettag.mobi>



bigtow.com

U.S.A. BUILT
EMPLOYEE OWNED




GALVANIZING
AVAILABLE

Photos may show optional equipment.

Deck-Over Tilt
B-25T

B-25T

ROCK-SOLID RELIABILITY



SPECIFICATIONS

S=Standard O=Optional

B-25T

CAPACITY / DIMENSIONS				
Payload Rating (lbs/kg)	50,000 / 22,680			
GVWR (lbs/kg)	62,000 / 28,123			
GAWR (lbs/kg)	54,480 / 24,712			
Approx. Avg. Weight (lbs/kg)	12,000 / 5443			
Overall Length (ft-in/mm)	36-8 / 11,176			
Deck Height (empty)(in/mm)	36 / 914			
Overall Width (ft-in/mm)	8-6 / 2591			
TONGUE				
Tongue Length 5'-2" (1575mm)	S			
Storage Tray with Lid	S			
Pintle Ring (in)	3			
High-Tensile Safety Chain	5/8" Grade 80			
Bolt-on Two-Speed Parking Jack	25K			
FRAME / RAMPS				
Main Beam	W16x26, Gr.50			
One-Piece Cold-Formed Frame Rails	S			
Side Rails (in x in x in)	8x2x1/4 Tubing			
Crossmembers	3" Jr I-beam			
Headboard Height (in/mm)	5.5 / 140			
Deck Length (ft/mm)	24+6 / 7315+1829			
Deck Material	2" nom. White Oak			
Deck Cushion Cylinder	S			
Deck Latch	Dual-Point			
Approach Ramp (in x in/mm)	18 / 457			
Load Angle (degrees)	10			
D-Ring Tie Downs (Total/Side)	10 / 5			
SUSPENSION / TIRES				
Adjustable Hutch 9700 Spring Suspension	S			
No. of Axles	3			
Axle Capacity (each) (lbs/kg)	22,500 / 10,206			
Axle Spread (in/mm)	49 / 1245			
Hubs	Oil Bath			
Brake Size (in/mm)	12.25x7.5 / 311x191			
Air Brakes (Full ABS Modulated, Park Brake All Axles)	S			
Hub Piloted Budd Wheels (in/mm)	17.5x6.75 / 445x171			
Wheel Bolt Pattern	8-bolt			
Tires / Load Range Rating	215/75R x 17.5 / H			

STANDARD EQUIPMENT


- Adjustable hitch height
- 7-pole round electrical plug
- Weather resistant sealed modular wiring
- Grommet mounted LED lights
- Registration holder
- Rust inhibiting primer
- Durable, rust inhibiting top coat
- Die-cut UV resistant vinyl decals
- D.O.T. approved conspicuity tape
- Mud flaps
- Trailer color: Equipment Charcoal

OPTIONAL EQUIPMENT

Other options may be available
See your dealer or visit our web site for details

- Rigid Gooseneck
- Dual parking jacks
- Additional stationary deck length
- Additional tie-downs
- Spare tire and wheel mount
- Spare tire and wheel
- Tire upgrade (235/75Rx17.5)
- Color options: Construction Yellow, Equipment Red, Equipment Blue, Equipment Black
- Galvanizing

Download these PDF specs to your Smart Phone. Scan this tag with your phone's camera using the app at <http://gettag.mobi>



*Listed GVWR, weights, and dimensions are for reference only. Manufacturer reserves the right to change models and specifications as they see fit. See our web site or your local authorized dealer for more information.